



SPECIFIC VEHICLE ALARM FITTING INSTRUCTIONS

REV. 00

www.cobra.it

MAKE	TOYOTA	MOD.	AVENSIS	YEAR	03 →		PETROL <input type="checkbox"/>
							DIESEL <input checked="" type="checkbox"/>

- | | |
|------------------------------|---|
| ALARM/SIREN POSITION | Position the compact alarms and the sirens on the support of the shock absorber, passenger's side. |
| CENTRAL UNIT POSITION | Position the modular systems and the modules under the dashboard driver's side. |
| POWER SUPPLY | +30: connect to the WHITE wire, in the second free slot of the fuse box. Add a 25Amp fuse.
-31: connect to a ground terminal located behind the driver's side bulkhead. |
| IGNITION WIRE | +15/54: connect to the BLACK/RED wire, in the light blue connector located behind the fuse box. |
| DIRECTION INDICATORS | Connect to the GREEN/WHITE and GREEN/YELLOW wires in the black connector of the direction indicators grey relay located behind the fuse box. |
| ELECTRIC WINDOWS | <p>Positive control signal</p> <p>Front window, driver's side:
cut the GREEN wire in the connector directly coming out of the driver's side window motor.</p> <p>Front window, passenger's side:
cut the GREEN/WHITE wire, at the position nr.13, in the 13 way white connector, behind the driver's side bulkhead.</p> <p>Rear window, driver's side:
cut the GREEN/BLACK wire, at the position nr.9, in the 13 way white connector, behind the driver's side bulkhead.</p> <p>Rear window, passenger's side:
cut the GREEN/YELLOW wire, at the position nr.11, in the 13 way white connector, behind the driver's side bulkhead.</p> |
| CENTRAL DOORS LOCKING | <p>Negative control signal</p> <p>Connect to the BROWN/WHITE wire (lock) and to the GREEN/WHITE wire (unlock), in the 24 way white connector behind the driver's side sill cover.</p> |
| IMMOBILISATION POINT | <p>Gasoil pump</p> <p>Cut the YELLOW wire, at the position nr.4, coming out of the connector behind the instrument panel.</p> |
| STARTER | +50: Cut the BLACK wire coming out of the 10 way white connector, located behind the passenger's side glove compartment. |
| BONNET SWITCH | Install an additional switch on the headlamp support plate, driver's side. |
| DOORS SWITCH | Connect to the RED wire at the position nr.4 in the driver's side door, and to the WHITE/GREEN wire at the position nr. 14, in the 18 way white connector, behind the driver's side sill cover for the rear doors; connect to the RED wire at the position nr.9, in the grey connector on the fuse box for the passenger's side door. Divide the lines with diodes 1N4004. |
| BOOT SWITCH | Connect to the RED/YELLOW wire in the wiring harness located in the sill cover of the driver's side door. |