

CAR SECURITY

SPECIFIC VEHICLE ALARM FITTING INSTRUCTIONS REV. 00						
www.cobra.it						
MAKE VOLVO	MOD.	V 40	YEAR	01 →	PETROL DIESEL	X
ALARM/SIREN POSITION	Position the compact side.	et alarms and the	sirens on t	he wheel h	ouse, passei	nger's
CENTRAL UNIT POSITION	The modular syste dashboard.	ms and the mod	dules shou	ld be posi	tioned unde	r the
POWER SUPPLY	+30: connect to the 4 out of the multiway co - 31: connect to one behind the left lateral	onnector at the entage of the terminals	rance of the coming out	fuse box.		
IGNITION WIRE	+ 15/54: connect to the on the locking central			nr. 4, in the	22 way conn	ector,
DIRECTION INDICATORS	Connect to the YELL connector, on the loc					green
ELECTRIC WINDOWS	Positive control sig Front window, driv driver's side door. Front window, pass driver's side door. Rear window, driver core hitch, driver's sid Rear window, passe core hitch, driver's sid	ers side: cut the sengers side: cut t ers side: cut the ' de door. engers side: cut the	he GREEN YELLOW/W	wire on the	serial push b	ootton,
CENTRAL DOORS LOCKING	Negative control sig Connect to the BRG (unlock) located in the central tunnel.	OWN/GREY wire	` '			
IMMOBILISATION POINT	Gasoil pump Cut the YELLOW/RI holder box, in the eng		OA fuse, ma	arked "ENG	INE", in the	relay
STARTER	+ 50: cut the GREEN key.	I wire located in the	e wiring har	ness cominç	g out of the ig	nition
BONNET SWITCH	Install an additional s	witch on the front h	ieadlamp su	ipport plate,	driver's side.	
DOORS SWITCH	Connect to the wires: GREEN (ant.left), GREEN/ORANGE (ant. right), GREEN/RED (post. left), LIGHT BLUE/YELLOW (post. right), in the 26 way green connector, on the central doors locking unit, located under the glove compartment, in the central tunnel.					
DOOT OWITCH	0	(DDO)((N)	1 - 00		. (6	

Connect to the BLUE/BROWN wire, in the 26 way connector, in the central doors

locking unit, located under the glove compartment, in the central tunnel.

BOOT SWITCH