



CAR SECURITY

SPECIFIC VEHICLE ALARM FITTING INSTRUCTIONS

REV. 00

www.cobra.it

MAKE

SUBARU

MOD.

IMPREZA

YEAR

96 →

PETROL
DIESEL

ALARM/SIREN POSITION

Position the compact alarms and the sirens in the engine compartment, on the panel of the wheel housing, passenger's side.
The modular systems and the modules should be fixed on the left, under the dashboard, driver's side.

POWER SUPPLY

+ **30**: connect to the ground terminal at the entrance of the fuse box.
- **31**: connect with a cable terminal to the car body.

DIRECTION INDICATORS

Connect to the BLACK/GREEN and WHITE/RED wires located in the wiring harness coming out of the 20 way blue connector, above the fuse box.

ELECTRIC WINDOWS

Positive control signal

Front window, driver's side:

cut the 1,5 mm² BLUE wire.

Front window, passenger's side:

cut the 1,5 mm² WHITE wire.

Rear window, driver's side:

cut the 1,5 mm² WHITE/RED wire.

Rear window, passenger's side:

cut the 1,5 mm² WHITE/BLUE wire.

The connections should be made in the wiring harness coming out of the 9 way connector on the base of the driver's side support.

CENTRAL DOORS LOCKING

Additional motor

It is necessary to install a 2 wires motor on the driver's side door.

IMMOBILISATION POINT

Fuel pump

Cut the 1,5 mm² YELLOW wire located in the wiring harness coming out of the round fuel pump relay, above the fuse box.

BONNET SWITCH

Install an additional switch on the front headlamp support plate, in correspondence with the left lateral headlamp.

DOORS AND BOOT SWITCH

Connect to the 1 mm² RED/GREEN wire located in the wiring harness coming out of the 20 way white connector, above the fuse box.